

Field descriptions

*

The following tables list the main tables in mSupply (There are some others, but we're not telling you about those!). This information will help you if you are building your own reports.

Note that if a field is indexed, finding information (querying) using that field will be very quick.

Main tables

Table	Description
Transactions	A transaction record is stored for each invoice
Transaction lines	one transaction line record is created for each line on an invoice
Items	An item record is created for each product or service purchased or supplied
Item lines	Each batch of stock at a particular location has one item_line record
Names	Each patient, customer or supplier has one name record
Purchase Orders	One record is created for each purchase order to a supplier
Purchase Order Lines	Each record is an order for one item on a purchase order
Quotes and Quote Lines	Quotations submitted by suppliers
Tenders	Tenders created to invite quote submissions from suppliers
Requisitions	Tables that store customer submitted stock and order data
Stock_take and Stock_take_lines	Stock takes and their related records
Store	Information about a particular virtual store
Drug_Register	Drug Registration records (for use in the Drug Registration module)

Foreign Keys

[Get your Foreign Keys here.](#)

Other tables

Table	Description
Abbreviations	Stores abbreviation codes and their expansion for dispensing directions
Account_code	Stores account codes associated with each item
Backorders	One record for <i>Customer</i> backorder.
Bill of Materials	One record for each mSupply user
Contacts	One record for each contact
Currency	One record for each currency
Drug interactions	Drug interactions and Drug interaction groups
Item Categories	One record for item category
Labels	Miscellaneous labels
Log	Each record contains one event recorded by mSupply
Users	One record for each mSupply user

Table	Description
Item Departments	The departments that an item can be assigned to
Item Directions	The default directions that are assigned to items
Item notes	The notes that are attached to items
Item Warning Link	A join table that stores which items have which warnings
Name category tables	Tables that store the categories that can be assigned to names (customers, suppliers, donors, manufacturers etc.)
Prescribers	One record for each prescriber
Regimen records, Regimen and Regimen Lines	Everything to do with storing ARV regimen records
Reminders	A reminder is an event with a due date- like a to-do
Stores	Stores and join tables that control access per-store
Warnings	The warnings which can be attached to items
Custom stock 5	Holds the details of the values that are selectable in the 5th user field when receiving stock
Custom stock 6	Holds the details of the values that are selectable in the 6th user field when receiving stock
Custom stock 7	Holds the details of the values that are selectable in the 7th user field when receiving stock.
Custom stock 8	Holds the details of the values that are selectable in the 8th user field when receiving stock

Tables used internally that you most likely shouldn't be interested in

Table	Description			
Number and Number re-use	Stores serial numbers such as invoice numbers			
Preferences	The data for each preference is in binary format. You're not interested.			
Item store join				
Field name	Description	Type	Length	Ind
Note that records are created for each item- there should always be one record for each item in each store				
id		Text		
store_ID		Text		
item_ID		Text		
inactive	true means item is not visible in this store. False means it is visible	bool		
Name store join				
Field name	Description	Type	Length	Ind
Note that records are only created as needed- that is a missing record implies the name is invisible for that store				
id		Text		
store_ID		Text		
name_ID		Text		
inactive	true means name is not visible in this store. False means it is visible	bool		
Name group				
Field name	Description	Type	Length	Ind
id		Text		

Name group				
Field name	Description	Type	Length	Ind
name		Alpha	40	
Name note				
Field name	Description	Type	Length	Ind
note_type		Alpha	3	
entry_date		Date		
note		Text		
name_key		Alpha	8	
id		Text		
Permissions				
Field name	Description	Type	Length	Ind
item_dept_id		Text		
name_group_id	Stores which name groups have permission to be supplied which item departments	Text		
Prefs				
Field name	Description	Type	Length	Ind
item	Internally used: storing preferences of text type(Now deprecated in favour of pref blob)	Alpha	20	
value		Alpha	60	
Reports				
Field name	Description	Type	Length	Ind
report_name		Alpha	80	
report_blob		BLOB		
owner_ID		Text		
id		Text		
last_updated		Date		
Ship method				
Field name	Description	Type	Length	Ind
id		Text		
method		Alpha	80	
Sync out				
Field name	Description	Type	Length	Ind
id		Text		
type	I=insert, U=update, D=delete	Alpha	2	
record_id	ID of the record to be synced	Text		
to_from_id	sync site ID to send the record	Long		
store_id	if store-specific data, the store ID for the record; blank → send to all sites	Text		
table_num	Internal table number of the record	Long		
table_id_num	Internal field number for the ID field of the record's table	Long		
Transaction category				
Field name	Description	Type	Length	Ind
id		Text		
category		Alpha	80	

Transaction category				
Field name	Description	Type	Length	Ind
type	"ci" for customer invoices "pi" for prescriptions "cc" for customer credits "si" for supplier invoices "sc" for supplier credits "sr for repacks "bu" for builds "in" for inventory adjustments	Alpha	3	
Transaction Notes				
Field name	Description	Type	Length	Ind
id		Text		
note		Text		
Units				
Field name	Description	Type	Length	Ind
id		Text		
units		Alpha	60	
comment		Text		

Previous: [Diagnostics](#) Next: [Finalising transactions](#)

From:

<https://docs.msupply.org.nz/> - mSupply documentation wiki

Permanent link:

https://docs.msupply.org.nz/admin:tables_fields?rev=1479117368

Last update:

2016/11/14 09:56

