

Training Handout: System Administration

3.02. Logging in

When mSupply starts you will be presented with the login window:



Username

Select your username from the list.

• Only users from your facility will be displayed. If the list is long, you can type the first few characters of your username in the *Search users* field to shorten the list to usernames that begin with what you have typed, sorted alphabetically.

- If you're just opening mSupply for the first time after installing it, select user 1(pass= user1).
- Each time it opens, mSupply will default to the user who last logged in.

Password

Enter your password. When this window opens, the focus is on the password field. This allows the user who last logged in to be able to quickly log in again.



If using the user 1(pass= user1) name, type user1 as the password.

Store

Select the store you want to log in to from the drop-down list.

- Most mSupply users will only be able to access a single store. For users who have access to
 more than one store, the login screen allows you to select any of the stores to which you have
 access. Once you have logged in you can switch the store without logging out see Switching
 stores.
- After selecting the desired store, all transactions you process will relate to that store.
- **Supervisors and other Level 1 users** will have an additional menu item, *Supervisor All stores*. In this mode, all stores are accessible. You would use this mode, for example, when placing an order for supplies that will be distributed to a number of stores or for reporting on more than one store see 26.07. Virtual stores.
- **HIS** if you have enabled the Hospital Info System (HIS) in the user login permission settings, and at least one licence is allocated to HIS (see HIS preferences), then you will also see *Hospital Info System* in the list of stores. If you select this, the login mode automatically changes to *HIS mode*.

In a synchronisation system (29.01. Introduction to Synchronisation) the user will see a list of all the *active* stores they have permission to log into in this datafile.

Messages

View any messages that might be displayed.

Click OK

Finally, click OK to login. If login is successful you will be taken to the navigator screen.



As with all windows in mSupply, pressing the Enter key at



any point produces the same result as clicking on the highlighted button, which, for this window, is the *OK* button. This facilitates fast keyboard control.

There are various options that can be set that cause a user to be taken to other screens or shown other information after logging in successfully. For example, Reminders or Invoices preferences.

Journal file

If one has not already been set up and if you are using a single user copy of mSupply, after logging in you will be asked to select the location for the journal file. A good place is to put it in the same folder as the datafile. You will only be asked to do this once.

The journal file is a place that mSupply records every database transaction that occurs after the last backup. It is used for repairing a damaged datafile and for investigating some types of errors.

Previous: 3.01. The tutorial like no other | | Next: 3.03. Opening the example data file

25.15. Managing users

About users and groups

User permissions are per-store, so a user can have different permissions when logged into different stores.

If you have many users that need to have the same permissions (because they carry out the same role, for example), you can create a group and assign the users to the group. Once a group is set up and permissions for the group assigned, any users that are assigned to the group will inherit the group's permissions, rather than having to set permissions for each user individually. When you change a group's permissions, you change the permissions for all users who belong to that group.

If you want to change a user's permissions and find out that all their permissions are greyed out and uneditable then it means they are a member of a group. To edit their permissions separately from the group, they must first be removed from the group:

- Edit the user, change the **Is a member of** drop down list to None, click **OK** (see below for details).
- Open the user again and their permissions will be editable.

Refer to Using groups below for more details. If the user is to remain part of the group then you must change the group's permissions (see Editing a group below) but beware,



this will change the permissions for all users who belong to the group, not just the user you're interested in.

If you want to disable a user, perhaps because the staff member has left the organisation, then they must be made 'inactive':

• Edit the user, uncheck the **Active** checkbox, click **OK**.



If the **Active** checkbox is greyed out, it is because they are a member of a group. You will need to first remove them from the group before you can make them 'inactive':

- Edit the user, change the Is a member of to None
- Edit the user, uncheck the Active checkbox, click OK.

Of course, if the whole group of users needs to be made inactive then you can just uncheck the **Active** checkbox for the group.

Adding and editing users and groups

mSupply has a comprehensive system of controlling user access, allowing you to manage in fine detail what each user can do and see in the system. You can manage users individually, in groups or a mixture of both - whichever is most suitable for your situation.

User access is managed by choosing **File > Edit users** from the menus, or by choosing **Admin > Edit users** in the Navigator. When clicking on this option you are presented with a list of current users:

-		Show:	Users		,
New User Permi	ssion report	Search	users		Q
User	Job title	Gro	ups	Active	
Advittame	Pharmacy Assistant			~	
Asertiu				1	
Bento	mSupply mobile us			~	
Bittitoro	Deputy Chief Phar			1	
DHE	Ag DHS			~	
Di	Deputy Secretary, I			~	
Foliti	Temporary staff (Ka			\checkmark	
Inestin	Assist. Medical Pro			1	
Igens	Chief Pharmacist			\checkmark	
Janon					
Kaitiim	Pharmacy Assistant			\checkmark	
Kansalinetenii	Temporary staff (Ta			~	
Kannen					
Kennis					
Kimilia	temporary staff (Ke			1	
kissimi	mSupply mobile us			~	
Manufactoria	Pharmacy Storeman			~	
Mattime	Pharmacy Assistant			1	
Me	Assist.Medical Proc			\checkmark	
Millio				~	
Moerman	Pharmacist (Wards	,		~	
OF	OPD Dr			~	
C	Temporany Staff (A	d		1	>
Double-click a user to	edit details			OK	

The list shows you the following information:

- User The user's name.
- Job title The user's job title, as entered on the details tab of the user's details form.
- **Group** The group the user belongs to. Will be blank of the user does not belong to a group.
- Active Checked if the user is allowed to login to the system.

To view groups rather than users, choose **Groups** from the **Show** Drop-down list at the top-right of the window. The list changes slightly to look like this:

00	G	roup list	
New group	Permission report	Show Groups	\$
	Group	Active	
Managers			
			_
			_
			_
			_
			_
ouble-click a u	ser to edit details		
			ОК
			UK

Now the list shows you slightly different information:

- Group The name of the group
- Active Checked if the group is active. If the group is active then all users in the group are allowed to login to the system. If the group is inactive (checkbox unchecked), all users in the group are inactive and are not allowed to login to the system.

To get a list of all current user permissions, click the **Permission Report** button. An Excel spreadsheet will be generated (see

sample

); it will have one worksheet for each store showing all the users and groups and what permissions they have in that store.

Double-click a user (or group) to edit their details or delete them. Click the **New User** button to add a new user (or the **New group** button to add a new group). Doing either will open the user details window (described below - for a new user or group all the tabs are empty, for an existing user or group the tabs are filled with their current settings)

User details window

User Gryffindor	r		
eneral Permissions Perm	issions (2) Permissions (3) Login rights Details		
is a member of Password	None	User can:	^
Confirm Password Active	☑	Use the Dashboard Receive email notifications Use web authorisation system	
an be responsible officer User Initials		٢	>
Language	English V	Signature	
Login using LDAP		Add Remov	
LDAP login string Windows Username		Add Remove	•
LDAP login string	None V		•
LDAP login string Windows Username License category	None V		•

This window has several tabs, all described below.

General tab

Is a member of

Used to select the user group the user belongs to (see below). When the window loads, it displays the group the user currently belongs to. It will show "None" if they are not a member of any group.

Password

This text box will always appear empty when the window is loaded. It must be set for a new user. It can be used here to change the password of an existing user.

Confirm password

If something is entered in the *Password* textbox, then the same text must be entered in this textbox. This step makes sure you set the password to what you think you're setting it to!

Active

If this checkbox is checked, then that user has permission to use the system, and their name will appear in the login window. If this checkbox is unchecked the user will not be allowed to login to the system and their name will not appear in the login window.

Can be responsible officer

If this checkbox is checked, the name of that user will appear for selection in the Responsible Officer selector on the Transport Details tab of a Customer invoice.

User initials

User initials should be entered in this field.

Language

Allows you to select which language the user wants to use in mSupply. As of August 2020, supported languages are:

- English
- French
- Lao
- Spanish
- Khmer
- Portuguese (partially complete)

LDAP section

This section can be used to check a user's login credentials against an LDAP (Lightweight Directory Access Protocol) server. If you are going to use LDAP you must fill in the server details in the General Preferences, LDAP tab first.

- Login using LDAP: Check this if you want this user's login details to be checked against your LDAP server. Means that you can have some users logging in normally and some being checked against your LDAP server. Helpful if there's a delay in users being given LDAP credentials for any reason.
- **LDAP login string**: Enter any string which has to be used with the LDAP login. Will be provided by the LDAP administrator if required.

Windows username

The username the user logs into window systems with. Used to provide single-sign-on capability when the user is logging in remotely to an mSupply client running on a Windows server.

2025/06/12 02:46

9/30

License category

Used to select which user license category the user belongs to. This will contain a list of all user categories currently set up in the datafile. See License management for details.

User belongs to State/Region

Used to select the name category 1 that the user belongs to. Only used in some customised versions of mSupply.

Signature

Use to add or remove an image of a user's scanned signature for displaying on invoices for example

Tags

Use to apply 'tags' to a user. These tags can then be used to control access to various features for users according to the tag.

User Can:

Used to give the following controls to users:

- Login as Desktop user
- Use the Dashboard this is necessary if you want the user to be able to see dashboards
- Receive email notifications this is necessary to enable reports to be emailed on a schedule to
 a user or group of users. Multiple reports for a User will appear on different tabs of an excel
 workbook. This needs to be configured by Sustainable Solutions, so get in touch if you're
 interested and we'll set this up for you.
- Use system if checked the user can login to the remote authorisation web app as an authoriser. See the 26.15. Remote authorisation page for details.



When a user is added to a group, the *User can* settings are set to those of the group i.e. they are inherited from the group. However, the *User can* section is still editable for an individual user - the settings are not controlled by the group after the user has been added to it.

Permissions tabs

These are where you can set access to the many features and functions on a store-by-store basis for each user or group. There are three Permissions tabs and each are shown in the screenshots below:



User Admin		Store: Lagos distribution centre
General Permissions Permissions (2) Permi	ssions (3) Open mSupply permissions Notifica	tions Login rights Details Dashboard
Names	Invoices	Invoices
Create customer, supplier & manufacturer names	Create customer invoices	Authorise customer invoices
View customer, supplier & manufacturer names	View customer invoices	 Authorise supplier invoices
	Edit customer invoices	Create cash transactions
Edit customer, supplier & manufacturer names	 Create supplier invoices View supplier invoices 	Pack boxes
Delete names	Edit supplier invoices	Create supplier credits
Edit name codes	Edit comments on finalised invoices	Builds and bill of materials
Edit name charge code	u	View cost prices on builds
Merge names	Import supplier invoices	Finalise builds
Edit name categories	 Duplicate supplier & customer invoices 	View bill of materials
Create & edit patient events	Finalise multiple invoices	Edit bill of materials
Add patients	Finalise customer invoices	Build items
Edit patient details	Finalise supplier invoices	Edit build items
View patients	Finalise repacks	Cash transactions
 Add and edit insurance policies 	 Finalise inventory adjustments 	Make cash payments
	Cancel finalised invoices	Receive cash
Add / edit name groups	Change transportation dates on finalised	Edit payment note field
Update master code	Edit user fields on finalised invoices	Transfers
Web interface	Edit user fields on finalised involces	 Transfer goods between stores
Edit web passwords	 Customer stocktakes: show internal analysis columns by default 	Finalise stock transfers
Edit and create web messages	Change invoice category on finalised	rinalise stock transfers
Reports	invoice	Printing
Manage reports	Return stock from customer involces	Print duplicate packing slips
Revert reports to original	Return stock from supplier invoices	Print duplicate packing sips
View reports	Overwrite total amount in prescriptions	

User Sussol		Store : GHSC-PSM Haiti Warehouse 😌
General Permissions Permissio	ns (2) Permissions (3) Notifications L	ogin rights Details Dashboard
Document management	Virtual Stores	Customer budgets
Fenders Upload tender document Download tender document	Create new stores Edit store details Edit visibility in stores	 Add/import customer budgets Edit/delete customer budgets
Delete tender document	Edit store credentials	Registration
Quotes Vpload quote document Download quote document	Reminders Edit and delete reminders assigned to me	Add/edit registrations
 Delete quote document Modify quotes entered by the supplier (via the website) Items Lines (Batches of Stock) Upload batch document Download batch document Delete batch document Stocktakes Create stocktake Delete stocktake Add stocktake lines View stocktake lines Edit stocktake lines Edit stocktake lines 	Admin Send email Purge old records View log Set start of year stock View/edit preferences Export & import Backup data file Vaccines View temperature breach configuration View and edit vaccine vial monitor status View sensor details Edit sensor location	Requisitions View requisitions Create and edit requisitions Administer finalised report type requisitions Create customer invoices from requisitions Supplier Hub View and edit supplier hub details Assets View assets Add/edit assets Setup assets Setup assets
 Delete stocktake lines Edit stocktake dates 	Replenishments Can be a worker Can authorise replenishments Can finalise replenishments	Change asset status

Buttons on the Permissions tabs

• The *Store* drop down list: Selects the store for which permissions are being displayed and set on the current tab. Select the store you want to see or set permissions for in this drop down list.

You can type in the drop down list. If you do this, when you click on the down arrow to open it, you will only be shown stores in the list which start with what you typed. Or, if you prefix it with the mSupply wildcard character, "@", you only see stores which contain what you typed. Very helpful if you have many, many stores and want to find a specific one or group of stores.

- The **All on** button: Checks all the permissions on the current tab i.e. turns them all on. There are exceptions to this for safety reasons; the *Update pack size, cost and sell price, Add/edit users* and *Access server administration* permissions on the **Permissions** tab are not turned on with the **All on** button.
- The **Copy** button: Copies the state of all the checkboxes on the tab for this store to an internal clipboard for that tab. From version 5.03 onwards, the button opens this window:

Permission tabs		
Desmissions		
Permissions	omSuppl	y permissions
Permissions (2)		
Permissions (3)		
Permissions (3)		
Stores		Selected
Drug Registration		
Gryffindor District Store		
Hogwarts Dispensary		
Hufflepuff Health Centre		
Slytherin Health Centre		
Supervisor- All stores		
	Cancel	ок

- In the *Permission tabs* section, select which tabs you want to copy the permissions from by checking their checkboxes.
- In the table, select the stores you want to copy the permissions of the current store to by checking them in the *Selected* column.
- Click the **OK** button to copy the selected permissions tabs of the current store to the selected stores. Click the **Cancel** button to close the window without doing anything.
- The **Paste** button: Only exists for versions before 5.03. Pastes the checkbox settings saved to the clipboard for the current tab to the same tab for another store. In this way, the Copy and Paste buttons are a great way of copying permission settings for tabs between stores really handy when users have similar permissions in different stores.

Most of the permissions are self explanatory. Those that need more explanation are given below:

Permission	Details	
Permissions Tab		
View stock	If not checked the user is not able to view the current stock list (see the 4.15. Show items with stock page), view the Stock tab of an item's details window (see the 4.01.05. Items - Stock tab page), not able to view stocktakes (see the 4.17. Stocktakes page) or view any reports in the <i>Stock and items</i> section on the <i>Reports</i> tab of the Navigator (see the 13.02. Stock and items reports page). If this permission is checked then they can do all these things unless they are prevented by not having other permissions e.g. if a user has this permission but they do not have the <i>View stocktakes</i> permission then they will still not be able to access Stocktakes.	

Permission	Details
Update pack size, cost and sell price	If checked the user is able to edit the pack size, cost and sell price of supplier invoice lines that have already had stock issued from them, <i>provided that the SI has not been finalised</i> . See the 7.01. Supplier invoices page for details.
Add/edit users	To prevent you being locked out of your datafile permanently, mSupply will not allow you to turn off this preference for the first 2 users which already exist when you open mSupply for the first time. You should always treat these users as admin users.
Access server administration	If this is checked the user will be able to access the server administration windows, as described on the 25.13. mSupply server administration page. Only assign this permission to users who really know what they are doing!
Add/edit sync sites	If checked the user is able to edit site settings in a synchronisation system (see the 29.02. Synchronisation Sites page for details). This includes being able to use the sync site wizard (29.03. Sync Site Wizard (Superseded)).
Disallow adding an unordered item to a Goods Received note	If checked the user is not able to add items to a goods received note that are not included on a purchase order (see the 7.02. Goods receipts page for details)
Permissions (2) Tab	
Add patients	If checked, the user can add new patients into the system
Edit patient details	If checked, the user can edit the details of patients already entered into the system. Of course, this means they can also view the details of patients in the system
View patients	If checked, the user can view patients' details in the system. If not checked then the user will not be able to see any patient details.
Change transportation dates on finalised invoice	If checked, the user can edit the Order written date , Order received date , Expected arrival date , Actual arrival date and Ship date fields on the <i>Transport details</i> tab of finalised customer invoices
Edit user fields on finalised invoices	The user fields are the 4 custom transaction fields that can be enabled in the preferences - see Invoices Preferences for details. If this is enabled the user can edit the contents of these fields on transactions that have already been finalised
Change invoice category on finalised invoice	If checked the user can edit the transaction category of invoices (customer, supplier and inventory adjustments)
Transfer goods between stores	If checked the user can create a customer invoice with a store as the customer (i.e create a stock transfer)
Finalise stock transfers	If checked the user can finalise a customer invoice where the customer is another store (i.e. a stock transfer)
Return stock from supplier invoices	If checked a <i>Return selected lines</i> button will appear for the user on finalised supplier invoices, allowing them to return the goods on the invoice. See the 9.01. Returning goods section for details
Return stock from customer invoices	If checked a <i>Return selected lines</i> button will appear for the user on finalised customer invoices, allowing them to return the goods on the invoice. See the 9.02. Receiving goods back from a customer section for details
Pack boxes	If checked the user is allowed to manage boxes and assign stock to boxes on a customer invoice, even if the user does not have the <i>Edit customer</i> <i>invoices</i> permission. See the 8.06. Box management page for details
Permissions (3) Tab	
Edit stocktake dates	If checked the user can edit the <i>Stock take date</i> field at the top of a stocktake and the confirmed date of inventory adjustments created from the stocktake (see Creating a new stocktake) for details

Permission	Details
Edit store details	If checked the user can edit the store details and preferences, including using the bulk store preferences editor.
Edit visibility in stores	If checked the user can edit the visibility of names and items in different stores. If it is unchecked they can't - either in the <i>Store</i> tab of a name or item's details window or the <i>Visibility</i> tab of a store's details window (in fact, the Visibility tab won't even be visible for them)
Add/import customer budgets	If this is checked the user can import or add budgets for a customer, if unchecked they cannot
View temperature breach configurations	If checked, the user can view temperature breach configurations in the vaccine/cold chain module. See the 20.01. Vaccine Vial Monitoring (VVM) page for details. Temperature breach configurations can only be edited in the Cold chain app or in mSupply mobile.
View and edit vaccine vial monitor status	If checked, the user can view and edit the statuses that vaccine vial monitors have. See the 20.01. Vaccine Vial Monitoring (VVM) page for details.
View sensor details	If checked the user can view temperature sensor details. See the 20.03. Cold Chain App Notifications page for details.
Edit sensor location	If checked the user can edit the warehouse location attached to a sensor. See the 20.03. Cold Chain App Notifications page for details.
Edit/delete customer budgets	If this is checked the user can edit or delete budgets for a customer, if unchecked they cannot
Create customer invoices from requisitions	If this is checked the user can create customer invoice from the <i>Create customer invoice</i> button on requisitions. You can use this in conjunction with the <i>Create customer invoices</i> permission on the Permissions (2) tab to force all distribution to be carried out from requisitions.
View assets	If this is checked, the user is allowed to search the assets in the system and see their details
Add/edit assets	If this is checked, the user can also change the details of assets
Setup assets	If this is checked a user can manage the setup of assets e.g. add or edit asset statuses, conditions, properties etc. (see the assets setup page for details of the various setup options)
Change asset status	If checked, the user can make an asset's proposed status its current status.

Notifications tab

On this tab, you determine what notifications (alerts) a user will see, and when they will see them:

User Admin	Store: Lagos distribution centre
General Permissions Permissions (2) Permissions (3) Open mSupply permission	Login rights Details Dashboard
Alert type	Is enabled
xpiring items	
verstocked items	
Inderstocked items	
Pending supplier invoices – status "nw"	
ending customer requisitions – status "sg"	
rending customer invoices - status "nw" or "sg"	
Pending customer credits - status "nw" or "sg"	
Overdue purchase orders	
	Pop up alerts Show notification window on login Show coldchain breach alerts
	Delete Cancel OK

To enable a particular alert type for a user simply check the checkbox in the *Is enabled* column. Any alert type that has its *Is enabled* checkbox unchecked will not be displayed for a user.

Show notifications window on login: If this is checked, as soon as a user logs in, the notifications window (displaying all the notifications they have selected in the table above), will be displayed for them. If this is unchecked, the notifications window will only be shown when the user clicks on the notifications icon on the Navigator:



Please note that the notifications displayed realte only to the store that the user is logged in to.

Show cold chain breach alerts: If this is checked the user will see temperature breach alerts (in the store in the **Store** drop down list above the table - this is a per store permission) passed to mSupply by the cold chain app (see https://docs.msupply.foundation/coldchain/introduction/ for details). If this is not checked then a user will not see temperature breach alerts that occur in this

store. Please note that a user must have login rights to a store to be able to see breach alerts, whether this permission is turned on or not.

Open mSupply permissions tab

User mSupply Support				Store: Central C	Contraceptives Warehous
General Permissions Permissions (2)	Permissions (3)	Open mSupply permissions	Notification	Login rights	Details Dashboard
Internal Order	Prog	ram permission			
Can confirm Internal Order as Sent	Sear	ch Program		Toggle view	Toggle edit
API Access		Program		View	Edit
Cold chain API access					
Admin					
Can modify central data					

This tab contains permissions that only affect Open mSupply users. Currently Open mSupply must connect to an existing mSupply server, which takes care of the authentication and synchronisation. Soon, when we've re-written the central synchronisation server in Open mSupply, there will be no need for this tab. Until then, permissions that only apply to users of Open mSupply will appear on this tab.

This tab is included in the permissions copying functionality of the **Copy** button at the bottom of the window (see the Buttons on the permissions tabs section for details).

Permission	Details
Can confirm internal order as sent	If checked then the user can <i>Finalise</i> an internal order in mSupply terms or <i>Send</i> it in Open mSupply terminology.
Cold chain API access	If checked then the username and password of this user can be used to access the cold chain REST API built into Open mSupply.
Can modify central data	If checked then the user can edit settings that are counted as central data in Open mSupply e.g. demographics indicators.

Permission	Details
	This section is used to define which programs this user is allowed to view or edit data for. The table will contain a list of all the Open mSupply programs that have been setup in the datafile and there will be checkboxes for each in the <i>View</i> and <i>Edit</i> columns.
Program permissions	Click on the appropriate checkboxes to check them and give the user the appropriate permissions. The Toggle view and Toggle edit buttons check or uncheck all the checkboxes in the <i>View</i> and <i>Edit</i> columns respectively.
	If the list of programs is long you can type something in the <i>Search programs</i> box to make the list display programs that contain what you typed only.

Login rights tab

On this tab you set which stores the user can login to:

sions (2) Permissions	(3) Open mSupply permissions	Notifications Login rights Details Dashboard			
Complex sea	arch	Toggle all in selection			
Is disabled	Default store	Can login			
		I			
		Image:			
		I			
	2				
	Complex sea	Complex search Is disabled Default store			

If there are too many stores in the list, you can restrict the display by typing in the *Search stores* text box: only stores with names starting with what you type will be displayed.

If you need a more complex type of search then click on the **Complex search** button and this filter window will open (you will recognise it as very similar to the customer or supplier search window):

ormal	Fuzzy
Name niter	
Name 😌	contains 🕤
and 🟮 Cate	igory 1 😑 is
and 🖸 C	ustomer group is Don't Care
Search	
All names	Manufacturers
 Selection 	Donors
Customers	✓ Exclude patients
Suppliers	Only stores
Exclude hidden names	
Com	plex Find Cancel Find

Make your filter selections as required, click on the **Find** button and only the stores which match the filters you have set will be displayed in the table.

The **Toggle all in selection** button turns on (checks) all the *Can login* checkboxes for all the stores shown in the list. Clicking it again will turn them off.

The *Is disabled* column indicates whether a store is disabled or not and can't be edited.

You can check one box in the *Default store* column - this will be the store the user is offered by default every time they login or switch stores.

In the *Can login* column you can check the box for each store the user is allowed to login to. All the stores in your mSupply datafile are displayed here in alphabetical order. Please note:

- The "Drug Registration" store is a special store used for the mSupply medicine registration functionality. See Registration for more details. Checking this box will allow the user to login to the Registration module.
- The "Hospital Info System" is another special store used for mSupply's built-in Hospital Information system. See here for more details. Checking this box will allow the user to login to the HIS module.
- "Supervisor All stores" stores is a special mode to allow users to view information in and run reports over multiple stores. See here for more information.

Sync user across all login stores: This checkbox is only displayed if the currently logged in user is designated as a "special user" and they are logged into the primary server in a synchronisation system (the server where the system data iis edited). If this is checkbox is checked, when the **OK** button is clicked the user's details are synchronised with all the stores they are allowed ot login to. In this way, an administrator in a synchronisation system is able to edit user permissions and settings and have them automatically synchronised to all relevant sites.

Details tab

2025/06/12 0	2:46
--------------	------

🖕 Edit user	
User Kekeia	
General Permissions Permissions (2) Permissions (3) Log-on modes Details	
Full name First name Last name	Date of birth 00/00/00
Dates Date created 10/11/2008 Date left 00/00/00	
Contact details	
Address 1 Phone 1	E-mail
Address 2 Phone 2	Job title
Supplier invoices with issued stock Can update pack size, cost and sell price	
	Delete Cancel OK

Here some personal details including job title, address and email address of the user can be recorded. The job title will appear in the *Job title* column in the list of users and the email address is used when using email functionality or other special functions in mSupply.

Other than that, these fields are for reference only, providing a handy place to record information about your system users.

Dashboard tab



On this tab you set which dashboard tabs will appear on the dashboard when the user logs into it. Of course, you have to set up the dashboard tabs before you can assign them to a user's dashboard. See Dashboard for instructions on doing that.

Once the dashboard tabs have been setup, they will appear in the *Available* column of this tab. You can see the "Test_tab" in the screenshot above. Anything in the *Chosen* column will be displayed on the user's dashboard. So, to make a dashboard tab appear on the user's dashboard, select it in the *Available* column and click on the >> icon to move the tab into the *Chosen* column. And to remove a dashboard tab from the user's dashboard, simply select it in the *Chosen* column and click on the << icon to move it back into the *Available* column.

Create a new user

To create a new user do this:

- 1. Go to *File > Edit users...* and click on the **New user** button
- 2. Enter the user name
- 3. Assign a password
- 4. Enter the password again in the Confirm password text box
- 5. Go to the permissions tabs and set up permissions (3 tabs) OR select which group the user is to belong to using the *Is a member of* drop down list on the General tab (you must do one of these because you'll have noticed that when you create a new user they have absolutely no permissions at all!)
- 6. Go to the Login rights tab and set the stores the user can login to.

- 7. Click **OK** when you're done.
- 8. The user should now be able to log in.
- 9. After the user logs in, they may want to change their password.

Delete a user or group

To delete a user do this:

- 1. Go to File > Edit users...
- 2. Double-click the name of the user or group you want to delete in the list
- 3. Click on the *Delete* button on the bottom of the edit user window that opens

Note that you won't be able to delete a group that has users belonging to it. If you really want to delete the group, remove all users from the group first by editing their *Is a member of* fields.

Managing and using groups

mSupply allows for a high granularity of user permission configuration. There are literally hundreds of user permissions possible for each store in an mSupply system. User groups assist with management of these user permissions.

- Users can be configured to:
 - Log in to particular stores
 - Have a range of general user permissions such as access to the dashboard
- Users can also be configured to have permission to view or edit data while logged in to particular stores.
- If users are a member of a group, then permission to view or edit data while logged in to particular stores is governed by the group membership.

A user can have permission to view or edit data while logged in to a particular store, either directly or through membership of a group. If you want the user to *exercise* these permissions then they will also need to have

permission to *log in* to the store

Adding a group

Show the list of groups by opening the "Edit user" window and then choosing "Groups" from the "Show" Drop-down menu

00		Group list
New group	Permission report	Show Groups =
	Group	Active
Managers		
Double-click a u	iser to edit details	
		ОК

To add a group, click the **Add Group** button. You will be shown a window where you add the group name. You then set permissions for the group in the same way as you set permissions for a user (above):

	Add new groups	
Group name Managers		
	General Permissions Permissions (2) Permissions (3) Log-on modes	_
Is a member of	None	
Password		
Confirm Password	Signature	
Active		
Can be responsible officer		
User Initials		
Language	English +	
LDAP Login using LDAP		
LDAP login string		
Low rogin string	Add Remove	
	Delete Cancel OK	
	You will only be able to set checkboxes which can have different settings in different stores. Anything that is not a checkbox and or any checkbox that applies across all stores cannot be set in a group's permissions (another way of saying this is that they cannot be controlled by a group). These items will all be disabled when creating or editing a group and are editable in the individual users' permissions only.	

Editing a group

First, show the list of groups by opening the "Edit user" window and then choosing "Groups" from the "Show" Drop-down menu:

00		Group list
New group	Permission report	Show Groups =
	Group	Active
Managers		
Double-click a u	ser to edit details	ОК

Then double click on a group in the list. The same window as for adding a group opens but it is populated with the group's current settings. Change these settings as described for a new group above and click on the **OK** button to save them.

Active users and groups

All permissions and most checkbox settings in a user settings are controlled by the group. One exception is login rights to different stores (managed for each user individually). Another exception is whether a user is active or not (active means that they are allowed to login to mSupply). By default, the active status of a group does not set the active status of all users in the group to match. However, you can make all users in a group inactive by editing the group and clicking on the **Update status** for all members button:

2025/06/12 02	2:46
---------------	------

			Edit group		
Group name Administra	ators				
	Permissions	Permissions (2)	Permissions (3)	Open mSupp	ply permissions Notifications
Is a member of	None		0	User can:	
Password Confirm Password					Login as Desktop user Use the Dashboard Receive email notifications
Active Can be responsible officer User Initials		date status for all	members		Use web authorisation system
Language LDAP	English	8		Signature	
Login using LDAP					Add Remove
				Tags	
License category	None		8		
User belongs to State/ Region	None				
					Delete Cancel OK

When you click on the **Active** checkbox for a group it does nothing except changee the state of the checkbox. However, when you click on the **Update status for all members** button, all members of the group have their *Active* status set to that of the checkbox in this group.

Using groups

Groups are a quick way of setting and managing permissions for many people at a time. Users belonging to a group take the permissions of that group: when a user is a member of a group you cannot edit their permissions directly, you must edit the group's permissions. And if you edit the group's permissions, you edit the permissions for every user in the group. To assign a user to a group, do the following:

- 1. Go to File > Edit users
- 2. Double click on the user you want to edit
- 3. On the general tab of the window which opens, use the *Is a member of* drop down list to select the group the user is to belong to:

	Ec	dit user
User user1		
(General Permissions Permissions (2)	Permissions (3) Log-on modes Details
Is a member of	f None +	
Password		
Confirm Password		
Active		Signature
Can be responsible officer		
User Initials		
Language	English +	
LDAP		
Login using LDAP	° 🗆	
LDAP login string	9	Add Remove
	· · · · · · · · · · · · · · · · · · ·	
		Delete Cancel OK

4. Click on the OK button to save you changes.

User license categories

A menu item on the Special menu of the navigator gives access to a form to view and edit user license categories, including the number of users belonging to them that can be logged in at any one time. A DDL on the user input form allows a user to be assigned to a category and a new permission covers the ability to edit these license categories and membership of them. Finally, a check on the OK button of the login form will check that there are less than the maximum users belonging to the license category the user belongs to already logged in.

Previous: 25.14. mSupply deployment || Next: 25.16. Show connected users

25.19. The system log

The log contains records of who did what and when in the system. It's a useful place to look to find out what happened to certain records and when certain things were done. Some events (lots!) are always logged by mSupply but some are optional and are chosen in the *Log* tab of the General preferences page.

To view the log, choose *View log...* from the *Special* menu. You will be shown all today's log entries when the window loads:

Export	Print.	Order by	Find From	n [15/10/2021] To [15/10/2021]	Today		0		
Date	Time	User	Type	Event		Source Table	Record ID	Extra information ((SON)	Store name
15/10/2021	09:48:35			store: General, Current users: Singl		user	A33525A6A7920F78	{"siteld":"0"}	General
15/10/2021	15:02:39			mSupply preferences have not been					General
15/10/2021	16:02:33	sussol	mSupply_pref_cancelled	mSupply preferences have not been	1 saved				General
									ОК

The columns contain this information:

- **Date:** the date when the log entry was made.
- Time: the time the log entry was made.
- **User:** the name of the user who did the operation giving rise to the log entry.
- **Type:** the type of log entry. Can be used for filtering or just telling you which part of the system generated the log entry.
- Event: a description of the event that occurred.
- Source table: the name of the table that contains the affected record (if there is one).
- **Record ID:** if there was one, the ID of the record in the database that was affected by the event.
- Extra information: detailed information about what happened in the event in JSON format. Not always provided.
- Store name: the name of the store that the event occurred in.

Buttons in the window:

- **Export** Export the log to a tab delimited text file. You can then import this into other applications (such as a spreadsheet application) for editing and printing.
- Print Prints the displayed list of log entries on your printer.
- Order by Sort the log by something than the default date/time order.
- Find Search for particular records in the log.
- **OK** Close the window.

Double-clicking a log entry in the list will bring up a read-only window showing the full log details:

• • •		Show log
Date:	24/01/2023	View data
Time:	09:22:17	
User:	mSupply Support	
Log ID:	E7A8F4A832864C03941D580E	
Record ID:	3EFA000BED164986A9E303F2I	
	Copy ID to Clipboard	
Event type:	login	
Event:	store: Main warehouse, Current users: Single User	
		ОК

- Date: The date the log entry was created
- Time: The time the log entry was created
- User: The name of the user whoi did the action that resulted in the log entry
- Log ID: The ID of thelog entry in the database
- Record ID: The ID of the record the log entry relates to e.g. the transaction that was edited
- **Copy ID to Clipboard button:** On click, copies the Record ID value to the Clipboard so you can poaste it somewhere else
- Event type: The type of the event that occurred. Used for filtering
- Event: Description of the event that occurred
- View Data button: On click, if the log entry has additional JSON information, it is displayed in the large panel below the button.

Dates

If you want to see log records that were generated over a different period then manually edit the dates in the **From** and **To** boxes as required or choose one of the many quick-select options in the drop down list to automatically set them (*Today* is selected by default):



Event types

Additionally, you can choose to show only certain types of event which occurred in the period you have selected. To do that, select one of the entries in the final drop down list on the right hand side (*All* is selected by default):



Custom query

If you are looking for log records that are not in the list of common event types described above, you will need to create a custom query. For example, to find a report of all the finalized POs this year:

- 1. Set the date / time period
- 2. Click on **Find**
- 3. Click on the small right arrow to the right of the first field box
- 4. Select the data type that you are looking for. In this case, we are looking for the event type
- 5. Type in the particular event type that we are looking for. In this case, we are looking for the finalized po
- 6. Click on Query
- 7. Once you are happy with the included results, click on **Print** (or **Export** to produce a text file that can be imported to Excel and manipulated)



Previous: 25.18. Label printer hardware setup || Next: 25.20. Server troubleshooting

